

Enforcer 2.5

The **Enforcer 2.5** is an extremely versatile 2.5 gallon portable firefighting system that utilizes high energy compressed foam technology. Enforcer One recommends using **FireAde²⁰⁰⁰** products which hold approvals with NFPA and UL.

FireAde²⁰⁰⁰ is a registered trademark of Fire Service Plus, Inc.

General Specifications – Standards

Out-diameter(mm): 180
Cylinder High(mm): 545
Cylinder weight(kg): 2.6
Extinguisher weight(kg): 12.2
Volume(L): 12.5
Filling Charge: **AFF-Water**
Temperature Range(°C): +5~+60
Working Pressure(bar): 15
Test Pressure(bar): 27
Material: **SUS304**

Simple Structure, flexible operation, convenient application

Fast extinguishing speed, high efficiency, continuous or intermittent spraying

Applicable to the extinguishment of initial fires caused by oil, flammable liquids, solid organics, gas, and electric equipment

Ideal equipment for use in factories, offices, schools, hotels, oil pump houses, filling stations, chemical paint houses, and combustible places

Cylinder and valve have obtained CE certificate

Cylinder surface is aluminum nature

enforcerone.com

Enforcer 2.5 is manufactured by Enforcer One, LLC.

Contact (678) 788-8413 for additional information or to schedule a demonstration.



ENFORCER