

The **Enforcer™ 60** is an extremely versatile 60 gallon portable firefighting system that utilizes high energy compressed foam technology. Enforcer™ One recommends using **FireAde²⁰⁰⁰** products which hold approvals with NFPA and UL.

FireAde2000 is a registered trademark of Fire Service Plus, Inc.

Performance

Pressure Vessel Capacity: **60 U.S Gallons**

Finished Foam Capacity: **Up to 1200 U.S. Gallons Finished Foam**

Throw Distance: **Up to 95 Feet**

Discharge Duration: **Up to 6 Minutes**

General Specifications – Standards

Pressure Vessel Construction: **Carbon Steel to ASME Code**

Pressure Vessel Dimensions: **20"x48"**

Fill Tower: **1 ½"**

System Hoses: **3000psi Hard Rubber Hose**

Plumbing: **All Stainless Steel With Brass Fill Cap**

Discharge Hose: **50' Lay Flat Hose**

Hose Storage: **Hose Tray**

Propellant Type: **Nitrogen or Compressed Air**

Propellant Cylinder Capacity: **Two 90 Cubic Foot Cylinders**

Propellant Cylinder Brackets: **3/8" Steel Placed in Frame Walls**

Discharge Nozzle: **1" Pistol Grip**

Discharge Nozzle Tip: **Power Tip Technology**

Wheels: **16" Flat Free Wheels**

Dimensions

Height: **38.5"**

Depth: **42"**

Length: **54.5"**

Empty Weight: **485 Pounds**

Loaded Weight: **985 Pounds**

Additional Options

Available with Hose Reel

Additional Nitrogen or Air Cylinders

Additional Hose Available in 50

or 100 ft Sections

Trailer Mount Option

Protective Cover



enforcerone.com

Enforcer™ 60 is manufactured by Fire Service Plus, Inc.

Contact (678) 788-841 for additional information or to schedule a demonstration.

60 Enforcer™