

FireAde®



FIREADE A/B	FIREADE AR 3X3	FIREADE CLASS A	FIREADE MIL-SPEC
Unique Dual UL Listed Class A & B Agent	UL 162 Listed at 3%	Application rates of .01-1%	Meets Military Specification MIL-PRF-24385F
UL 162 Listed	LASTFIRE Certified at 1%	P/H neutral, non corrosive	Listed on QPL-24385
NFPA 18 Listed	Low Viscosity at 900cps	Completely water soluble	Unlimited Shelf Life
Meets EN 1568 & ICAO Level B approved	Flows through gravity fed foam systems	Unlimited shelf life	Non Corrosive, will not clog or gum equipment
Unlimited Shelf Life	25yr shelf life	Economically Priced	NSN # 4210-01-056-8343
Effective on Class D Fires	Non Corrosive, will not clog or gum equipment	Non Corrosive, will not clog or gum equipment	NSN # 4210-01-056-0883
Non Corrosive, will not clog or gum equipment			NSN # 4210-01-139-4972 NSN # 4210-01-144-0291



FIREADE TRAINING FOAM	FIREADE CLIMATE CONTROL CONCENTRATE	FIREADE CLIMATE CONTROL PRE-MIX	GREEN AGENT TECHNOLOGY™
Perfect for Class A application training	Tested to -40c as a concentrate	Pre Mixed with water	<ul style="list-style-type: none"> • Environmentally Formulated • Organic Compounds • Zero Hazardous Chemicals • Encompasses Water Based and Food Grade Ingredients • Biodegradable • Contains no ingredients reportable under the Superfund amendments and Reauthorization Act (SARA) Title III, Section 313 of 40 CFR-372 or Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA).
Non Corrosive, will not clog or gum equipment	Climate control option available on any product	Designed especially for fixed systems	
1%,3%,6% usage	Suitable for Class A & B Fires	Tested to -40c in solution	
Unlimited Shelf Life	Perfect for outdoor foam cache	Suitable for Class A & B Fires	
	Non Glycol Based Product	Non Glycol Based Product	
	Non Corrosive, will not clog or gum equipment	Climate control option available on any product	
		Non Corrosive, will not clog or gum equipment	

ENFORCER

PORTABLE CAFS TECHNOLOGY



MODEL	ENFORCER 3 SUPER DUTY	ENFORCER 3 BACK PACK	ENFORCER 10	ENFORCER 30 SKID
PRE-MIX CAPACITY	3 US Gallons	3 US Gallons	10 US Gallons	30 US Gallons
FINISHED FOAM CAPACITY	60 US Gallons	60 US Gallons	200 US Gallons	600 US Gallons
THROW DISTANCE	45 Feet	45 Feet	45 Feet	45 Feet
DISCHARGE DURATION	1 Minute	1 Minute	2:30 Minutes	7:30 Minutes
DISCHARGE HOSE	4 Ft. x 3/8" Booster	4 Ft. x 3/8" Booster	70 Ft. x 1/2" Booster	70 Ft. x 1/2" Booster
HEIGHT	22.5"	22.5"	22"	32"
WIDTH	13"	13"	22"	30.5"
LENGTH	8.25"	8.25"	26"	26"
EMPTY WEIGHT	23 Lb	23 Lb	95 Lb	136 Lb
LOADED WEIGHT	48 Lb	48 Lb	175 Lb	388 Lb



MODEL	ENFORCER 60	ENFORCER 60 SKID	ENFORCER 200
PRE-MIX CAPACITY	60 US Gallons	60 US Gallons	200 US Gallons
FINISHED FOAM CAPACITY	1200 US Gallons	1200 US Gallons	4000 US Gallons
THROW DISTANCE	95 Feet	95 Feet	120 Feet
DISCHARGE DURATION	6 Minutes	6 Minutes	20 Minutes
DISCHARGE HOSE	50 Ft. x 1" Lay Flat	50 Ft. x 1" Lay Flat	300' x 1" Booster 50Ft. x 1.5" Lay Flat
HEIGHT	38.5"	30.5"	45"
WIDTH	42"	35"	44"
LENGTH	54.5"	50"	98"
EMPTY WEIGHT	485 Lb	238 Lb	1200 Lb
LOADED WEIGHT	985 Lb	747 Lb	2800 Lb
CERTIFICATIONS	UL 711	UL 711	UL 711